

## CLAIMS

I claim:

- 1           1. A mechanic's creeper, comprising:
  - 2           a hollow tubular main frame having at least a left side
  - 3 member, a right side member, and a head crossmember;
  - 4           a frame extension having at least a left side member, a
  - 5 right side member, and a foot crossmember, with the left side
  - 6 member and the right side member of said frame extension
  - 7 telescopingly disposed respectively within the left side member
  - 8 and the right side member of said main frame;
  - 9           a back rest pad secured to said main frame;
  - 10          a buttocks support cushion removably attached to said frame
  - 11 extension;
  - 12          a left and a right head end wheel depending from said main
  - 13 frame, near said head crossmember thereof; and
  - 14          a left and a right foot end wheel depending from said frame
  - 15 extension adjacent said foot crossmember thereof.

- 1           2. The mechanic's creeper according to claim 1, further
  - 2 including a tool and equipment storage compartment disposed
  - 3 between said left side member and said right side member of said
  - 4 main frame, and below said back rest pad.

1           3.   The mechanic's creeper according to claim 1, further  
2 including a storage and carrying case therefor.

1           4.   The mechanic's creeper according to claim 1, further  
2 including a left and a right arm rest removably attached  
3 respectively to said left side member and said right side member  
4 of said main frame.

1           5.   The mechanic's creeper according to claim 4, further  
2 including a tool storage pouch foldably depending from each said  
3 arm rest.

1           6.   The mechanic's creeper according to claim 1, further  
2 including at least one adjustably positionable work light  
3 extending from said main frame adjacent said head crossmember  
4 thereof.

1           7.   The mechanic's creeper according to claim 1, further  
2 including a warning light removably attached to said main frame.

1           8. A mechanic's creeper, comprising:  
2           a hollow tubular frame assembly having at least a left side  
3 member, a right side member, a head crossmember, and a foot  
4 crossmember;  
5           a tool and equipment storage compartment disposed between  
6 the left side member and the right side member of said frame  
7 assembly;  
8           a back rest pad hingedly secured to one of the side members  
9 of said frame assembly and over said tool and equipment storage  
10 compartment; and  
11           a left and a right head end wheel, and a left and a right  
12 foot end wheel, the wheels depending from said frame assembly.

1           9. The mechanic's creeper according to claim 8, wherein  
2 said frame assembly comprises:

3           a hollow tubular main frame having at least a left side  
4 member, a right side member, and a head crossmember;

5           a frame extension having at least a left side member, a  
6 right side member, and a foot crossmember, with the left side  
7 member and the right side member of said frame extension  
8 telescopingly disposed respectively within the left side member  
9 and the right side member of said main frame; and

10          a buttocks support cushion removably attached to said frame  
11 extension.

1           10. The mechanic's creeper according to claim 8, further  
2 including a storage and carrying case therefor.

1           11. The mechanic's creeper according to claim 8, further  
2 including a left and a right arm rest removably attached  
3 respectively to said left side member and said right side member  
4 of said frame assembly.

1           12. The mechanic's creeper according to claim 11, further  
2 including a tool storage pouch foldably depending from each said  
3 arm rest.

1        13. The mechanic's creeper according to claim 8, further  
2 including at least one adjustably positionable work light  
3 extending from said frame assembly adjacent said head  
4 crossmember thereof.

1        14. The mechanic's creeper according to claim 8, further  
2 including a warning light removably attached to said frame  
3 assembly.

1           15. A mechanic's creeper, comprising:

2           a hollow tubular frame assembly having at least a left side  
3 member, a right side member, a head crossmember, and a foot  
4 crossmember;

5           a back rest pad secured to said main frame;

6           a left and a right head end wheel, and a left and a right  
7 foot end wheel, the wheels depending from said frame assembly;  
8 and

9           a storage and carrying case configured for storing and  
10 carrying therein, at least said frame assembly including said  
11 back rest pad and each said wheel.

1        16. The mechanic's creeper according to claim 15, wherein  
2 said frame assembly comprises:

3        a hollow tubular main frame having at least a left side  
4 member, a right side member, and a head crossmember;

5        a frame extension having at least a left side member, a  
6 right side member, and a foot crossmember, with the left side  
7 member and the right side member of said frame extension  
8 telescopingly disposed respectively within the left side member  
9 and the right side member of said main frame; and

10       a buttocks support cushion removably attached to said frame  
11 extension.

1        17. The mechanic's creeper according to claim 15, further  
2 including a tool and equipment storage compartment disposed  
3 between said left side member and said right side member of said  
4 frame assembly, and below said back rest pad.

1        18. The mechanic's creeper according to claim 15, further  
2 including a left and a right arm rest removably attached  
3 respectively to said left side member and said right side member  
4 of said frame assembly.

1        19. The mechanic's creeper according to claim 18, further  
2 including a tool storage pouch foldably depending from each said  
3 arm rest.

1        20. The mechanic's creeper according to claim 15, further  
2 including:

3            at least one adjustably positionable work light extending  
4 from said frame assembly adjacent said head crossmember thereof;  
5 and

6            a warning light removably attached to said frame assembly.